

Here we present the most popular and common products from our wide selection. For any other format or model, consult our experts. They will be able to find the right product for your specific project.

# QUICK CONVERSION CHARTS

Litres	Imperial Gallon	US Gallon	Cubic Metre	Cubic Centimetre	Cubic Inch
Ltr	Imp. Gal/IG	US Gal	m <sup>3</sup>	cm <sup>3</sup>	in <sup>3</sup>
0.001	0.00022	0.000264	0.000001	1	0.061024
0.0164	0.003605	0.004329	0.000016	16.4	1
1	0.22	0.264201	0.001	1,000	61
3.79	0.832701	1	0.003785	3,785	231
4.55	1	1.2	0.004545	4,545	277
28.317	6.229712	7.481333	0.028317	28,317	231
159	35	42	0.15897	158,970	9,701
1,000	220	264	1	1,000,000	61,024

**Note:**

Plastic tanks can be used to contain liquids (excluding flammable liquids / hydrocarbons) with a specific gravity of up to 1.7. Recommended maximum constant operating temperature is 140° F (moulded polyethylene itself is rated for 140° F). If a liquid is ruled to only be stored in a glass or steel container, then this tank should never be used to store that liquid. Any liquid approved to be stored in a plastic container would be suitable to be stored in these tanks.

Please request a drawing to confirm shape and dimensions are suitable.